KELVA Brakes

B0.6, B1.5, B3.0





Improved Quality

With KELVA's High or Low Friction Brakes

- Fully air operated
- Constant web tension
- · Easy to maintain and install
- Reliable high quality standards
- Three different sizes, each available with high or low friction brake pads

Kelva brakes are designed for many different applications. Our three brake sizes, all of which can be equipped with high or low friction pads, cover braking requirements for a wide variety of materials. As they are pneumatic and therefore explosion-proof, they can be used in conditions where electrically operated brakes would be unacceptable.


Dovey Corp. is an authorized distributor for all Kelva Products 3220 W. 25th St., Anderson, IN 46018, Phone: (800) 457-2576 Sales Rep: Gary Lovelace & Associates, Cell: (850) 206-3823 Office Phone: (850) 469-9708, E-Mail: gelgcas@bellsouth.net




PRODUCT DESCRIPTION

Product name	Kelva Brakes B0.6, B1.5 and B3.0		
Brake pads	Can be connected to operate on 2, 4 or 6 brake pads		
Control	Pneumatic and air cooled		
Shaft standards	B0.6 - 25mm B1.5 - 35, 32.5, 30mm B3.0 - 40, 35 and 32.5mm		
Safety	Explosion proof		

DIMENSIONS



Dimensions								
Model	Shaft Ø	Α	В					
B0.6	25mm	220mm	Ø180mm					
B1.5	35, 32,5 and 30mm	260mm	Ø220mm					
B3.0	40, 35 and 32,5mm	370mm	Ø342mm					



Brake	Brake pads		Max bro	ake power	Max brak	e torque
	Low friction	High friction	hp	kW	kpm	Nm
B0,6 - 6	Х		0,6	0,44	6	60
B0,6 - 9		Χ	0,6	0,44	9	90
B1,5 - 9	Х		1,5	1,1	9	90
B1,5 - 15		Χ	1,5	1,1	15	150
B3 - 30	Χ		3,0	2,2	30	300
B3 - 50		Χ	3,0	2,2	50	500



Your Authorized Kelva Distributor is: Dovey Corp., 3220 W. 25th St., Anderson, IN 46018

Your Dovey Sales Representative is:
Gary Lovelace & Associates, 3670 Baisden Rd., Pensacola, FL 32503
Office Phone (850) 469-9708, Cell Phone (850) 206-3823
E-Mail: gelgcas@bellsouth.net, Web Site: www corrugatedonline.net
07 Kelva Brake 2018